

Air impact wrenches

M2062 >

Impact Wrench, 1/2" Drive

- Twin Hammer
- Light Weight, Aluminium & Composite
- 3 Forward Speed & 2 Reverse Speed
- Maximum Torque 1356 Nm

Specifications

Square Drive	1/2"
Bolt Capacity	5/8" (16mm)
Free Speed	10000 Rpm
Max Torque	1356 Nm
Torque Forward	950 Nm
Torque Reverse	1020 Nm
Air Consumption	153 L/min
Air Inlet	1/4"
Air Pressure	6,3 BAR
Air Hose	10 mm



< M2072

Impact Wrench Set, 15 Pc 1/2" Drive
Incl. Sockets

- Twin Hammer
- Light Weight, Aluminium & Composite
- 3 Forward Speed & 2 Reverse Speed
- Maximum Torque 1356 Nm

Contents

M2062 1/2" Composite Impact Wrench (Twin Hammer)
Impact Deep Socket with Plastic Sleeve: 17 - 19 - 21 mm
Impact Deep Socket: 22 - 23 - 24 mm
Oil Pot
L-Hex Key 4mm
Nipple
Mini Oiler

Packing specification:

M2062 Carton: 10 - N.W.(Kgs): 20.8 - G.W.(Kgs): 21.8 - CBM: 0.04

M2072 Carton: 5 - N.W.(Kgs): 21.8 - G.W.(Kgs): 22.8 - CBM: 0.05



Air impact wrenches

M2034 >

Air Impact Wrench, 3/4" Drive Twin Hammer

- 3/4" Twin Hammer
- Light Weight, High Torque
- 3 Forward Speed & 3 Reverse Speed
- Maximum Torque 1630 Nm

Specifications

Square Drive 3/4"
Bolt Capacity 1 1/8" (28mm)
Free Speed 5500 Rpm
Max Torque 1630 Nm
Torque Forward 1290 Nm
Torque Reverse 1356 Nm
Air Consumption 195 L/min
Air Inlet 3/8"
Air Pressure 6,3 BAR
Air Hose 13mm

Packing specification:

Carton: 6 - N.W.(Kgs): 21 - G.W.(Kgs): 22.5 - CBM: 0.044



M2016 >

Impact Wrench, 1" Drive

- Pinless Mechanism
 - Powerfull Torque Output
- Adjustable Torque
 - 3 Forward Torque Settings
 - 3 Reverse Torque Settings
- Comfortable, Ergonomic Design
 - Ergonomically Designed for the operator's comfort
 - Long Type with 6" (15cm) Anvil

Specifications

Square Drive 1"
Free Speed 5000 Rpm
Max Torque 2712 Nm
Torque Forward 1742 Nm
Torque Reverse 1827 Nm
Air Consumption 255 L/min
Air Inlet 1/2" (12,70mm)
Air Pressure 6,2 BAR
Air Hose 3/4" (19,05mm)

Packing specification: Carton: 2 - N.W.(Kgs): 16.7 - G.W.(Kgs): 19.2 - CBM: 0.037

Cordless Impact wrenches

M2033 >

1/2" Impact

Specifications

Voltage	18 V d.c.
No-Load speed	1800 Rpm
Max Torque	6000kg-cm / 588 Nm / 430 ft-lb
Tool weight	
(with battery)	3kg (battery 0.53kg)
Capacity	1/2" (13mm)
Charging time	1 hour Auto Cut - off

comes with two batteries



< M2038

3/8" Mini cordless

Specifications

Voltage	18 V d.c.
No-Load speed	2000 Rpm
Max Torque	2450kg-cm / 240 Nm / 177 ft-lb
Tool weight	
(with battery)	2kg (battery 0.53kg)
Capacity	3/8" (10mm)
Charging time	60-70 Minuten Auto Cut - off

comes with one battery

M2041 >

Battery

Specifications

18V, 3.0 Ah li-ion battery
suitable for M2033 - M2038



M2042 >

Battery charger

Specifications

2,3A Li-ion 18V battery charger
suitable for M2033 - M2038

